

SDS ID No.: AMNS-0007

Safety Data Sheet (SDS)

Section 1 – Identification

1(a) Product Identifier Used on Label: Mill Scale

1(b) Other Means of Identification: AMNS-0007, Scalebreaker Sludge, Cooling Tower Grit

1(c) Recommended Use of the Chemical and Restrictions on Use: None

1(d) Name, Address, and Telephone Number:

AM/NS Calvert LLC

Phone number: 251-289-3000

P.O. Box 456


Calvert, AL 36513

1(e) Emergency Phone Number: 1-760-476-3962 (Verisk 3E Company Code: 333211) or CHEMTREC (Day or Night): 1-800-424-9300

Section 2 – Hazard(s) Identification

2(a) Classification of the Chemical: Mill Scale is considered a hazardous material according to the criteria specified in REACH [REGULATION (EC) No 1907/2006] and CLP [REGULATION (EC) No 1272/2008] and OSHA 29 CFR 1910.1200 Hazard Communication Standard. The categories of Health Hazards as defined in “GLOBALY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS), Third revised edition ST/SG/AC.10/30/Rev. 3” United Nations, New York and Geneva, 2009 have been evaluated. Refer to Section 3, 8 and 11 for additional information.

2(b) Signal Word, Hazard Statement(s), Symbols and Precautionary Statement(s):

Hazard Symbol	Hazard Classification	Signal Word	Hazard Statement(s)
	Carcinogenicity - 1A	DANGER	May cause cancer.

Precautionary Statement(s):

Prevention	Response	Storage/Disposal
Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.	If exposed or concerned: Get medical advice/attention.	Dispose of contents in accordance with federal, state and local regulations. Store locked up.

2(c) Hazards not Otherwise Classified: None Known

2(d) Unknown Acute Toxicity Statement (Mixture): None Known

Section 3 – Composition/Information on Ingredients

3(a-c) Chemical Name, Common Name (Synonyms), CAS Number and Other Identifiers, and Concentration:

Chemical Name	CAS Number	EC Number	% weight
Mill Scale, ferrous metal	65996-74-9	266-007-8	100%
The following components comprise this product and were used for hazard determination:			
Iron and Iron Oxides	1345-25-1 1309-38-2 1309-37-1 7439-89-6	215-721-8 215-169-8 215-168-2 231-096-4	70-99
Silicon Oxides and Compounds including Crystalline Silica (as Quartz)	7631-86-9 7440-21-3 14808-60-7	231-545-4 231-130-8 238-878-4	0-1.5

EC- European Community

CAS- Chemical Abstract Service

Note: Mill Scale is comprised of primarily of iron oxides with calcium, manganese and magnesium oxides and compounds along with carbon, oil and greases.

Section 4 – First-aid Measures

4(a) Description of necessary measures: If exposed, concerned: Get medical advice/attention.

- Inhalation:** If inhaled: Remove person to fresh air and keep comfortable for breathing.
- Eye Contact:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing.

Section 4 – First-aid Measures (continued)

4(a) Description of necessary measures (continued):

- **Skin Contact:** If on skin: Wash with plenty of water.
- **Ingestion:** If swallowed: Call a poison center or doctor/physician if you feel unwell.

4(b) Most Important Symptoms/Effects, Acute and Delayed (Chronic):**Acute effects:**

- **Inhalation:** Excessive exposure to high concentrations of dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract.
- **Eye:** Particles of iron or iron compounds may become imbedded in the eye. Excessive exposure to high concentrations of dust may cause irritation to the eyes.
- **Skin:** Skin contact with dusts may cause irritation, possibly leading to dermatitis. Skin contact with metallic dusts may cause physical abrasion.
- **Ingestion:** Ingestion of dust may cause nausea and/or vomiting.

Chronic Effects:

Individuals with chronic respiratory disorders (i.e., asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any airborne particulate matter exposure. Persons with pre-existing skin disorders may be more susceptible to dermatitis.

4(c) Immediate Medical Attention and Special Treatment: Treat symptomatically.

Section 5 – Fire-fighting Measures

5(a) Suitable (and Unsuitable) Extinguishing Media: Use extinguishers appropriate for surrounding materials.

5(b) Specific Hazards Arising from the Chemical: Not applicable for solid product.

5(c) Special Protective Equipment and Precautions for Fire-fighters: Self-contained NIOSH approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

Section 6 - Accidental Release Measures

6(a) Personal Precautions, Protective Equipment and Emergency Procedures: For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust. Personnel should be protected against contact with eyes and skin. Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid using compressed air. Do not release into sewers or waterways.

6(b) Methods and Materials for Containment and Clean Up: Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations. Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal requirements.

Section 7 - Handling and Storage

7(a) Precautions for Safe Handling: Wear protective gloves / protective clothing / eye protection / face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Emergency safety showers and eye wash stations should be present.

7(b) Conditions for Safe Storage, including any Incompatibilities: Whenever feasible, store locked up.

Section 8 - Exposure Controls / Personal Protection

8(a) Occupational Exposure Limits (OELs): The following exposure limits are offered as reference, for an experienced industrial hygienist to review.

Ingredients	OSHA PEL ¹	ACGIH TLV ²	NIOSH REL ³	IDLH ⁴
Iron and iron oxides	10 mg/m ³ (iron oxide fume)	5.0 mg/m ³ (iron oxide, respirable fraction ⁵)	5.0 mg/m ³ (iron oxide dust and fume)	2,500 mg/m ³ (as Fe)
Crystalline Silica (as Quartz)	0.05 mg/m ³ “AL” 0.025 mg/m ³	0.025 mg/m ³ (as respirable fraction)	0.05 mg/m ³ (as respirable dust), Ca	50 mg/m ³ (as quartz, Tripoli) 25 mg/m ³ (as cristobalite, tridymite), Ca
Oils and Greases	5.0 mg/m ³	NE	5.0 mg/m ³ “STEL” 10 mg/m ³	2,500 mg/m ³

NE - None Established

1. OSHA PELs (Permissible Exposure Limits) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A (“C”) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday. An Action level (AL) is used by OSHA and NIOSH to express a health or physical hazard. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL, but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.

Section 8 - Exposure Controls / Personal Protection (continued)

8(a) Occupational Exposure Limits (OELs) (continued):

- Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. ACGIH TLVs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes. DSEN – May cause dermal sensitization. This notation is used to indicate the potential for dermal sensitization resulting from the interaction of an absorbed agent and ultraviolet light (i.e. photosensitization). RSEN – May cause respiratory sensitization.
- The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL)- Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
- The "immediately dangerous to life or health air concentration values (IDLHs)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994. Ca is designated as carcinogen.
- Respirable fraction. The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in ACGIH 2018 TLVs ® and BEIs ® Appendix D, paragraph C.

8(b) Appropriate Engineering Controls: Local exhaust ventilation should be used to control the emission of air contaminants. General dilution ventilation may assist with the reduction of air contaminant concentrations. Emergency eye wash stations and deluge safety showers should be available in the work area.

8(c) Individual Protection Measures:

- Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure and powered-air do not protect workers in oxygen-deficient atmospheres.

- Eyes:** Wear eye protection/face protection. Chemical goggles, face shields or glasses should be worn to prevent eye contact. Contact lenses should not be worn where industrial exposure to this material is likely.
- Skin:** Persons handling this product should wear appropriate clothing to prevent skin contact. Wear protective gloves.
- Other protective equipment:** An eyewash fountain and deluge shower should be readily available in the work area.

Section 9 - Physical and Chemical Properties


9(a) Appearance (physical state, color, etc.): Metallic grey /black dust, flake or scale	9(j) Upper/Lower Flammability or Explosive Limits: NA
9(b) Odor: Organic and occasionally metallic odor	9(k) Vapor Pressure: NA
9(c) Odor Threshold: NA	9(l) Vapor Density (Air = 1): NA
9(d) pH: ND	9(m) Relative Density: 6.7 (approx.) SG
9(e) Melting Point/Freezing Point: ~2400°F	9(n) Solubility(ies): Water <0.1% Insoluble
9(f) Initial Boiling Point and Boiling Range: NA	9(o) Partition Coefficient n-octanol/water: NA
9(g) Flash Point: NA	9(p) Auto-ignition Temperature: ND
9(h) Evaporation Rate: NA	9(q) Decomposition Temperature: ND
9(i) Flammability (solid, gas): Not flammable	9(r) Viscosity: ND
NA - Not Applicable ND - Not Determined for product as a whole	

Section 10 - Stability and Reactivity

- 10(a) Reactivity:** Not Determined (ND)
- 10(b) Chemical Stability:** Mill Scale is stable under normal storage and handling conditions.
- 10(c) Possibility of Hazardous Reaction:** None Known
- 10(d) Conditions to Avoid:** Storage with strong acids or calcium hypochlorite.
- 10(e) Incompatible Materials:** Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.
- 10(f) Hazardous Decomposition Products:** Thermal oxidative decomposition of this product can produce fumes containing oxides of carbon and other metallic oxides.

Section 11 - Toxicological Information

11 Information on Toxicological Effects: The following toxicity data has been determined for **Mill Scale** by using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of OSHA and the EU CPL. Individual hazard classification categories where the available toxicological data has met or exceeded a classification threshold are provided in the table below:

Hazard Classification	Hazard Category		Hazard Symbols	Signal Word	Hazard Statement
	EU	OSHA			
Carcinogenicity (covers Categories 1A, 1B and 2)	NR	1A ^g		Danger	May cause cancer.

* NR Not Rated - Available data does not meet criteria for classification.

Below is additional toxicological data regarding this product:

a. No LC₅₀ or LD₅₀ has been established for **Mill Scale**. The following data has been determined for the components:

- **Iron Oxide:** LD₅₀ = >10,000 mg/kg (Oral/ Rat)
- **Iron:** Rat LD₅₀ = 1060 mg/kg (IUCID) (oral)
- **Silica :** Rat LD₅₀ = 500 mg/kg (Oral/ Rat)

b. No Skin (Dermal) Irritation data available for **Mill Scale** as a mixture. The following Skin (Dermal) Irritation data has been determined for the components:

- **Iron Oxide:** Moderately irritating.
- **Iron:** Irritating when administered as Iron metal. Rabbit Draize – irritating (IUCID)

c. No Eye Irritation data available for **Mill Scale** as a mixture. The following Eye Irritation information was found for the components:

- **Iron Oxide:** Severely irritating; may cause burns. Human Corrosive (IUCID).
- **Crystalline Silica:** May cause abrasion of the cornea.

d. No Skin (Dermal)/Respiratory Sensitization data available for **Mill Scale** as a mixture or its individual components.

e. No Aspiration Hazard data available for **Mill Scale** as a mixture or its individual components.

f. No Germ Cell Mutagenicity data available for **Mill Scale** as a mixture. The following Germ Cell Mutagenicity information was found for the components:

- **Iron Oxide:** Both positive and negative data.

g. Carcinogenicity: IARC, NTP, and OSHA do not list **Mill Scale** as carcinogens. The following Carcinogenicity information was found for the components:

- **Silicon Dioxide:** IARC-1 (silica, crystalline), carcinogen to humans; ACGIH TLV-A2 (silica, crystalline), suspected human carcinogen; NTP-K, known to be a carcinogen; NIOSH-Ca, potential occupational carcinogen; OSHA-Ca, carcinogen.
- **Iron Oxide:** IARC-3, unclassifiable as to carcinogenicity in humans; ACGIH TLV-A4, not classifiable as a human carcinogen.

h. No Toxic Reproduction data available for **Mill Scale** as a mixture or its individual components.

i. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for **Mill Scale** as a mixture. The following STOT following a Single Exposure data was found for the components:

- **Silicon Dioxide:** Single exposure to very high airborne levels may cause lung irritation in exposed humans.
- **Iron Oxide:** May cause lung irritation.
- **Iron:** Irritating to Respiratory tract.

j. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for **Mill Scale** as a whole. The following STOT following Repeated Exposure data was found for the components:

- **Silicon Dioxide:** Repeated exposure to crystalline silica causes silicosis and kidney damage as well as increased incidence of autoimmune disorders in humans.
- **Iron Oxide:** Some pulmonary and lung effects reported from Iron oxide exposure in humans.

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2018, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS), European Union Classification, Labeling and Packaging, (EU CPL), Regulation on Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), International Uniform Chemical Information Database (IUCID), TOXicology Data NETwork (TOXNET), European Risk Assessment Reports (EU RAR).

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s):

Acute Effects by Component:

- **IRON (IRON OXIDE):** Iron is harmful if swallowed, causes skin irritation, and causes eye irritation. Contact with iron oxide has been reported to cause skin irritation and serious eye damage.
- **CRYSTALLINE SILICA (Silicon Dioxide):** Causes irritation and inflammation of the respiratory tract. May cause abrasion of the cornea. Inhalation may cause cough. A single exposure to very high airborne levels may cause lung irritation in exposed humans.

Delayed (chronic) Effects by Component:

IRON (IRON OXIDE): Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign lung disease, called siderosis, which is observable as an X-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation

Section 11 - Toxicological Information (continued)

of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. Iron oxide is listed as a Group 3 (not classifiable) carcinogen by the International Agency for Research on Cancer (IARC).

- **CRYSTALLINE SILICA (Crystalline Quartz):** Inhalation of quartz is classified by IARC as a probable human carcinogen. Chronic exposure can cause silicosis, a form of lung scarring that can cause shortness of breath, reduced lung function, and in severe cases, death. Repeated exposure may cause kidney damage as well as increased incidence of autoimmune disorder.

Section 12 - Ecological Information

12(a) Ecotoxicity (aquatic & terrestrial): No data available for the product, **Mill Scale** as a whole. However, individual components of the product have been found to be toxic to the environment. Dusts may migrate into soil and groundwater and be ingested by wildlife as follows:

- **Iron Oxide:** LC₅₀: >1000 mg/L; Fish
- **Calcium Oxide:** LC₅₀: 159 mg/L; invertebrates

12(b) Persistence & Degradability: No Data Available

12(c) Bioaccumulative Potential: No Data Available

12(d) Mobility (in soil): No Data Available

Additional Information:

Hazard Category: NA

Signal Word: No Signal Word

Hazard Symbol: NA

Hazard Statement: NA

Section 13 - Disposal Considerations

Disposal: Dispose of in accordance with Local, State, Federal and International regulations. Observe safe handling precautions.

Container Cleaning and Disposal: Follow Local, State, Federal and international regulations. Observe safe handling precautions

Section 14 - Transport Information

14 (a-g) Transportation Information:

US Department of Transportation (DOT) under 49 CFR 172.101 does not regulate **Mill Scale** as a hazardous material. All Local, State, Federal and international regulations that apply to the transport of this type of material must be adhered to.

Shipping Name: NOT DOT Regulated Shipping Symbols: NA Hazard Class: NA UN No.: NA Packing Group NA DOT/IMO Label: NA Special Provisions (172.102): NA	Packaging Authorizations a) Exceptions: NA b) Non-bulk: NA c) Bulk: NA	Quantity Limitations a) Passenger Aircraft or Rail: NA b) Cargo Aircraft Only: NA Vessel Stowage Location: NA DOT reportable quantities: NA
--	---	--

International Maritime Dangerous Goods (IMDG) and the Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID) classification, packaging and shipping requirements follow the US DOT Hazardous Materials Regulation.

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR) does not regulate **Mill Scale** as a hazardous material.

Shipping Name: NOT DOT Regulated Classification Code: NA UN No.: NA Packing Group: NA ADR Label: NA Special Provisions: NA Limited Quantities: NA	Packaging a) Packing Instructions: NA b) Special Packing Provisions: NA c) Mixed Packing Provisions: NA	Portable Tanks & Bulk Containers a) Instructions: NA b) Special Provisions: NA
--	--	---

International Air Transport Association (IATA) does not regulate **Mill Scale** as a hazardous material.

Shipping Name: NOT DOT Regulated Class/Division: NA Hazard Label (s): NA UN No.: NA Packing Group: NA Excepted Quantities (EQ): NA	Passenger & Cargo Aircraft Limited Quantity (EQ)		Cargo Aircraft Only: Pkg Inst: NA Max Net Qty/Pkg: NA	Special Provisions: NA ERG Code: NA
	Pkg Inst: NA	Pkg Inst: NA		

Pkg Inst – Packing Instructions

Max Net Qty/Pkg – Maximum Net Quantity per Package

ERG – Emergency Response Drill Code

Mill Scale does not have a **Transport Dangerous Goods (TDG)** classification.

Section 15 - Regulatory Information

Regulatory Information: The following listing of regulations relating to an AM/NS Calvert LLC product may not be complete and should not be solely relied upon for all regulatory compliance responsibilities.

This product and/or its constituents are subject to the following regulations:

EPA Regulations: The product, **Mill Scale** is not listed as a whole in the following regulatory listings. However, individual components of the product are listed:


Components	Regulations
Manganese Oxide (Mn Compounds)	SARA 313
Manganese	CERCLA, CAA, SARA 313,

SARA Potential Hazard Categories: Immediate Acute Health Hazard, Delayed Chronic Health Hazard.

Section 313 Supplier Notification: The product, **Mill Scale** contains the following toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372:

CAS #	Chemical Name	Percent by Weight
7439-96-5	Manganese (Mn Compounds)	2 max

State Regulations: The product, **Mill Scale** as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

- Pennsylvania Right to Know (RTK): Contains regulated material in the following categories:
- Hazardous Substances: Iron Oxide, Calcium, Calcium Oxide, Aluminum, Magnesium (compounds), Silicon, Silica Quartz
 - Environmental Hazards: Aluminum, Manganese
- California Prop. 65:  This product can expose you to chemicals including silica, crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer; and does not contain chemicals which is known to the State of California to cause reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
- New Jersey: Contains regulated material in the following categories:
- Hazardous Substance: Calcium, Calcium Oxide, Aluminum (dust and fume), Magnesium, Magnesium Oxide, Manganese, Manganese (compounds), Silicon, Silica Quartz
 - Special Health Hazard Substances: Calcium, Calcium Oxide, Aluminum (dust and fume), Manganese, Silicon, Silica Quartz
 - Environmental Hazards: Manganese, Manganese (compounds)
- Minnesota: Magnesium Oxide, Manganese, Silica Quartz
- Massachusetts: Iron Oxide, Calcium, Calcium Oxide, Aluminum (dust and fume), Magnesium, Magnesium Oxide, Manganese, Manganese (compounds), Silicon, Silica Quartz

Other Regulations:

WHMIS Classification (Canadian): The product, **Mill Scale** is not listed as a whole. However individual components are listed.

Ingredients	WHMIS Classifications
Magnesium	Flammable Solids – Category 2
Calcium	Substances which, in contact with water, emit flammable gases - Category 2; Combustible dusts*
Calcium Oxide	Skin corrosion/irritation - Category 1; Serious eye damage/eye irritation - Category 1; Health hazards not otherwise classified (corrosion) - Category 1
Silicon	Flammable solids - Category 2 (The classification "Flammable solids" refers to the amorphous form of silicon powder); Combustible dusts**
Quartz	Carcinogenicity - Category 1A; Specific target organ toxicity - repeated exposure - Category 1
Manganese	Reproductive toxicity - Category 2; Specific target organ toxicity - repeated exposure - Category 1; Combustible dusts*

* This product could belong to the hazard class "Combustible dust", based on various factors related to the combustibility and explosiveness of its dust, including composition, shape and size of the particles

** This product belongs to the hazard class "Combustible dust" if 5% or more by weight of its composition has a particle size < 500 µm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information

Prepared By: AM/NS Calvert LLC

Original Date of Issue: 05/22/2015


Revised Date: 3/15/2021

Additional Information:

Hazardous Material Identification System (HMIS) Classification

Health Hazard	1
Fire Hazard	0
Physical Hazard	0

National Fire Protection Association (NFPA)



Section 16 - Other Information (continued)

Hazardous Material Identification System (HMIS) Classification

HEALTH= 1, * Denotes possible chronic hazard if airborne dusts or fumes are generated. Irritation or minor reversible injury possible.

FIRE= 0, Materials that will not burn.

PHYSICAL HAZARDS = 0, Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.

National Fire Protection Association (NFPA)

HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment is given.

FIRE = 0, Materials that will not burn.

INSTABILITY = 0, Normally stable, even under fire exposure conditions, and are not reactive with water.

ABBREVIATIONS/ACRONYMS:

ACGIH	American Conference of Governmental Industrial Hygienists	NIF	No Information Found
BEIs	Biological Exposure Indices	NIOSH	National Institute for Occupational Safety and Health
CAS	Chemical Abstracts Service	NTP	National Toxicology Program
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	ORC	Organization Resources Counselors
CLP	Classification, Labelling and Packaging	OSHA	Occupational Safety and Health Administration
CFR	Code of Federal Regulations	PEL	Permissible Exposure Limit
CNS	Central Nervous System	PNOR	Particulate Not Otherwise Regulated
GI, GIT	Gastro-Intestinal, Gastro-Intestinal Tract	PNOC	Particulate Not Otherwise Classified
HMIS	Hazardous Materials Identification System	PPE	Personal Protective Equipment
IARC	International Agency for Research on Cancer	ppm	parts per million
LC50	Median Lethal Concentration	RCRA	Resource Conservation and Recovery Act
LD50	Median Lethal Dose	REACH	Regulation on Registration, Evaluation, Authorization and Restriction of Chemicals
LD_{Lo}	Lowest Dose to have killed animals or humans	RTECS	Registry of Toxic Effects of Chemical Substances
LEL	Lower Explosive Limit	SARA	Superfund Amendment and Reauthorization Act
LOEL	Lowest Observed Effect Level	SCBA	Self-contained Breathing Apparatus
LOAEC	Lowest Observable Adverse Effect Concentration	SDS	Safety Data Sheet
µg/m³	microgram per cubic meter of air	STEL	Short-term Exposure Limit
mg/m³	milligram per cubic meter of air	TLV	Threshold Limit Value
mppcf	million particles per cubic foot	TWA	Time-weighted Average
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit
NFPA	National Fire Protection Association		

Disclaimer: This information is taken from sources or based upon data believed to be reliable. Our objective in sending this information is to help you protect the health and safety of your personnel and to comply with the OSHA Hazard Communication Standard and Title III of the Emergency Planning and Community Right-to-Know Act. AM/NS Calvert LLC makes no warranty as to the absolute correctness, completeness, or sufficiency of any of the foregoing, or any additional, or other measures that may not be required under particular conditions. THIS AM/NS CALVERT LLC SDS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY, OR ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, AND ANY IMPLIED WARRANTIES OTHERWISE ARISING FROM COURSE OF DEALING OR TRADE.

Mill Scale

Signal Word: DANGER

Symbols:



HAZARD STATEMENTS:

May cause cancer.

PRECAUTIONARY STATEMENTS

Wear protective gloves/protective clothing/eye protection/face protection.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If exposed or concerned: Get medical advice/attention.

Dispose of contents in accordance with federal, state and local regulations.

Store locked up.

SDS ID No.: AMNS-0007

AM/NS Calvert LLC

P.O. Box 456

Calvert, AL 36513

General Information: Phone: 251-289-3000

CHEMTREC (Day or Night): 1-800-424-9300

Emergency Contact: 1-760-476-3962, (Verisk 3E Company Code: 333211)

Original Issue Date: 5/22/2015

Revised: 3/15/2021